



REQUIREMENTS: DOM: 14-31818 MHz  
 INTERNATIONAL: 14-187576 MHz  
 Y2 4.33418 MHz

FOR REQUIREMENTS: DOM: UM1652  
 INTERNATIONAL: PAL B/GERMANY (CH. 4)  
 PAL I/UK (CH. 36)

ITORS ARE 2N3904.  
 ARE IN-4188.

RS ARE MEASURED IN OHMS. SK. K. KATT.  
 URS ARE MEASURED IN MICROFARADS.

S-UNLESS OTHERWISE SPECIFIED:

- U7 U5 IS AN ALTERNATE FOR THE CUSTOM GATE ARRAY AND MUST BE USED IN COMBINATION WITH A PAL46B
- 10. CAPACITORS MARKED WITH AN ASTERISK (\*) ARE NON-ASLORIZED.
- 9 OSC MODULE FREQUENCY REQUIREMENTS:  
 DOM: 14.31818 MHz  
 INTERNATIONAL: 14.187576 MHz
- 8 ADD JUMPER W2 FOR DOMESTIC.
- 7 NOT REQUIRED FOR DOMESTIC UNITS.

LAST REFERENCE DESIGNATION	
PROG. 208	U53 07 08S A1 Y3
REFERENCE DESIGNATION	
RM. 32.04-48	C49, 52
97-109.112-115	47, 77, 1
154-199	106, 106-1, 109